



XE360™ SERIES WIRELESS TUBULAR LOCK



XE360 Tubular Exterior
with Latitude lever



XE360 Tubular Interior
with Latitude lever

Finish codes and descriptions

619	622	626
Satin Nickel (US15)	Matte Black (US19)	Satin Chrome (US26D)

The XE360™ Series is the next generation of wireless electronic lock from Schlage. Its sleek design offers customers a solution that looks as good as it performs—at an affordable price point. Schlage XE360 currently works within No-Tour or offline access control systems and is built to accommodate changing technologies. Credential support includes smart, Bluetooth and NFC mobile. The XE360 Series is available as tubular, mortise, mortise deadbolt, or exit trim. The open architecture design of the XE360 allows it to be managed by ENGAGE™ and other Allegion software or be integrated into popular physical access control and Proptech systems through Allegion's PACS Alliance program. This enables customers to choose what best fits their requirements now and in the future.

Standard features

- Next level design inside and out
- Credential support includes Schlage MIFARE®, Bluetooth® and NFC mobile¹
- Advanced encryption keeps data and communications safe
- Wireless configuration using connected smartphones or tablets
- No-Tour or offline system capacity
- Open architecture – interoperable and simple for software alliances to integrate
- Works seamlessly with other Schlage wireless locks, including Schlage Control®²
- Uniquely concealed key override standard on all locks

1. Use of mobile credential is dependent on availability of compatible mobile credential.
2. Check with your Proptech or PACS provider for specific support.

Mechanical specifications

Chassis	Tubular	Door range	1-3/4" (44mm)
Handing	On-site handing with included hex key	Construction	All-metal chassis and escutcheon; exterior polycarbonate elements
Latch	1" x 2-1/4" (25mm x 57mm); square and round corner faceplate; 1" (25mm) edge bore required	Levers	Zinc
Strike	Standard: 1-1/8" (29mm) lip, ANSI, 1-1/8" x 2-3/4" (29mm x 70mm), no box; Optional: Additional strike lip lengths and ANSI strike box available	Cylinder and keys	Schlage Classic C keyway, Conventional 6-pin cylinder with two keys
Strike width	Minimum 4-1/4" (108mm)	Certifications	ANSI/BHMA A156.02-2022 Grade 2 ANSI/BHMA A156.25-2023 Locked outdoor type ANSI/BHMA A156.5-2020
Backset	Standard: 2-3/4" (70mm), field adjustable to 2-3/8" (60mm)		

Reader specifications

Credential technologies	Smart (13.56 MHz), Bluetooth Low Energy (LE) (2.4 GHz), and Near Field Communication (NFC)	Smart credential support	Secure application area: Schlage MIFARE Classic®, Schlage MIFARE® DESFire® EV1/EV2/EV3 CSN only: HID iCLASS®, HID iCLASS SE®, MIFARE Classic / DESFire
Read range	Smart: up to .5" Bluetooth® Low Energy: up to 15' NFC: mobile device dependent	Mobile credential support	Schlage Mobile Bluetooth Credential, Integrated PACS mobile credential with Bluetooth, Apple Wallet® NFC student ID and employee badge; Google Wallet™ NFC student ID and employee badge
Standards	ISO standard 15693 and ISO 14443		



XE360™ SERIES WIRELESS TUBULAR LOCK

SELECT LOCK MODEL		
Description	Specify	Price (ea.)
Tubular	XE360-T	\$849.00

SELECT LOCK MODEL		
Description	Specify	Price adjustment
Offline – Toured and No-Tour compatible	OF	No charge

SELECT FUNCTION		
Description	Specify	Price adjustment
Indicator (LED indicator on interior assembly)	I	No charge
Button (Interior Push Button with LED indicator)	B	No charge

SELECT READER		
Description	Specify	Price adjustment
Smart/NFC Mobile (13.56 MHz) and Bluetooth® (2.4 GHz) Mobile Credential Support	SM	No charge

SELECT LEVER STYLE		
Description	Specify	Price adjustment
Broadway	BRW	No charge
Latitude	LAT	No charge
Neptune	NEP	No charge
Longitude Extended Length	LON-E	No charge

SELECT FINISH STYLE		
Description	Specify	Price adjustment
Satin Nickel	619	No charge
Matte Black	622	No charge
Satin Chrome	626	No charge

SELECT KEY CYLINDER		
Description	Specify	Price adjustment
Schlage Conventional, 6-pin	P6	No charge

SELECT KEYWAY		
Description	Specify	Price adjustment
Schlage Classic Obverse	C	No charge



XE360™ SERIES WIRELESS TUBULAR LOCK

SELECT STRIKE		
Description	Specify	Price adjustment
Strike, 1-1/8" lip – Standard	A500-074	No charge
Strike, 1-1/2" lip	A500-077	No charge
Strike, 1-3/4" lip	A500-079	No charge
Strike, 2" lip	A500-081	No charge

SELECT DOOR THICKNESS		
Description	Specify	Price adjustment
1-3/4" Thick door	134	No charge

SELECT DOOR POSITION SWITCH		
Description	Specify	Price adjustment
Less door position switch – Standard	LLL	No charge

SELECT SOLD SEPARATE		
Description	Specify	Price (ea.)
Mount, XE360 Series Tubular	47709952	\$281.00
Condensation sealant kit (includes PCBA cover, backplate plugs, and gaskets for environmental robustness)	47870663	\$55.00
Door position switch	47467230	\$45.00



XE360™ SERIES WIRELESS MORTISE LOCK



XE360 Mortise Exterior
with Broadway lever



XE360 Mortise Interior
with Broadway lever

Finish codes and descriptions

619	622	626
Satin Nickel (US15)	Matte Black (US19)	Satin Chrome (US26D)

The XE360™ Series is the next generation of wireless electronic lock from Schlage. Its sleek design offers customers a solution that looks as good as it performs—at an affordable price point. Schlage XE360 currently works within No-Tour or offline access control systems and is built to accommodate changing technologies. Credential support includes smart, Bluetooth and NFC mobile. The XE360 Series is available as tubular, mortise, mortise deadbolt, or exit trim. The open architecture design of the XE360 allows it to be managed by ENGAGE™ and other Allegion software or be integrated into popular physical access control and Proptech systems through Allegion's PACS Alliance program. This enables customers to choose what best fits their requirements now and in the future.

Standard features

- Next level design inside and out
- Credential support includes Schlage MIFARE®, Bluetooth® and NFC mobile¹
- Advanced encryption keeps data and communications safe
- Wireless configuration using connected smartphones or tablets
- No-Tour or offline system capacity
- Open architecture – interoperable and simple for software alliances to integrate
- Works seamlessly with other Schlage wireless locks, including Schlage Control®²
- Uniquely concealed key override standard on all locks

1. Use of mobile credential is dependent on availability of compatible mobile credential.
2. Check with your Proptech or PACS provider for specific support.

Mechanical specifications

Chassis	Mortise	Door range	1-3/4" (44mm)
Handing	On-site handing with included hex key	Construction	All-metal chassis and escutcheon; exterior polycarbonate elements
Latch	Standard: 3/4" (19mm) throw stainless steel latch bolt with anti-friction tongue	Levers	Zinc
Strike	Standard: 1-3/16" (30mm) curved lip, ANSI, 1-1/4" x 4-7/8" (32mm x 124mm); no box Optional: Additional strike lip lengths and ANSI strike box available	Cylinder and keys	Schlage Classic C keyway, Conventional 6-pin cylinder with two keys
Strike width	Minimum 4-1/2" (114mm)	Certifications	ANSI/BHMA A156.13-2022 ANSI/BHMA A156.25-2023 Locked outdoor type ANSI/BHMA A156.5-2020
Backset	2-3/4" (70mm)		

Reader specifications

Credential technologies	Smart (13.56 MHz), Bluetooth Low Energy (LE) (2.4 GHz), and Near Field Communication (NFC)	Smart credential support	Secure application area: Schlage MIFARE Classic®, Schlage MIFARE® DESFire® EV1/EV2/EV3
Read range	Smart: up to .5" Bluetooth® Low Energy: up to 15' NFC: mobile device dependent	Mobile credential support	CSN only: HID iCLASS®, HID iCLASS SE®, MIFARE Classic / DESFire Schlage Mobile Bluetooth Credential, Integrated PACS mobile credential with Bluetooth, Apple Wallet® NFC student ID and employee badge; Google Wallet™ NFC student ID and employee badge
Standards	ISO standard 15693 and ISO 14443		



XE360™ SERIES WIRELESS MORTISE LOCK

SELECT LOCK MODEL		
Description	Specify	Price (ea.)
Mortise	XE360-M	\$1,059.00

SELECT LOCK MODEL		
Description	Specify	Price adjustment
Offline – Toured and No-Tour compatible	OF	No charge

SELECT FUNCTION		
Description	Specify	Price adjustment
Indicator (LED indicator on interior assembly)	I	No charge
Button (Interior Push Button with LED indicator)	B	No charge
Deadbolt (Interior Thumbturn with LED indicator) – Mortise chassis with deadbolt included	D	\$100.00

SELECT READER		
Description	Specify	Price adjustment
Smart / NFC Mobile (13.56 MHz) and Bluetooth® (2.4 GHz) Mobile Credential Support	SM	No charge

SELECT LEVER STYLE		
Description	Specify	Price adjustment
Broadway	BRW	No charge
Latitude	LAT	No charge
Neptune	NEP	No charge
Longitude Extended Length	LON-E	No charge

SELECT FINISH		
Description	Specify	Price adjustment
Satin Nickel	619	No charge
Matte Black	622	No charge
Satin Chrome	626	No charge

SELECT KEY CYLINDER		
Description	Specify	Price adjustment
Schlage Conventional, 6-pin	P6	No charge

SELECT KEYWAY		
Description	Specify	Price adjustment
Schlage Classic Obverse	C	No charge



XE360™ SERIES WIRELESS MORTISE LOCK

SELECT ARMOR FRONT		
Description	Specify	Price adjustment
Button and indicator 1-1/4" x 8" x 7/32"	09-663	No charge
Deadbolt 1-1/4" x 8" x 7/32"	09-666	No charge

SELECT STRIKE		
Description	Specify	Price adjustment
Mortise strike, 1-3/16" lip with screws – Standard	10-072	No charge

SELECT DOOR THICKNESS		
Description	Specify	Price adjustment
1-3/4" Thick door	134	No charge

SELECT DOOR POSITION SWITCH		
Description	Specify	Price adjustment
Less door position switch – Standard	LLL	No charge

SELECT SOLD SEPARATE		
Description	Specify	Price (ea.)
Mount, XE360 Series Mortise	47709953	\$281.00
Condensation sealant kit (includes PCBA cover, backplate plugs, and gaskets for environmental robustness)	47870663	\$55.00
Door position switch	47467230	\$45.00



XE360™ SERIES WIRELESS EXIT WIDE STILE LOCK



XE360 Exit Exterior
with Neptune lever



XE360 Exit Interior
with Falcon Rim 25R
(exit device sold separately)

Finish codes and descriptions

619	622	626
Satin Nickel (US15)	Matte Black (US19)	Satin Chrome (US26D)

The XE360™ Series is the next generation of wireless electronic lock from Schlage. Its sleek design offers customers a solution that looks as good as it performs—at an affordable price point. Schlage XE360 currently works within No-Tour or offline access control systems and is built to accommodate changing technologies. Credential support includes smart, Bluetooth and NFC mobile. The XE360 Series is available as tubular, mortise, mortise deadbolt, or exit trim. The open architecture design of the XE360 allows it to be managed by ENGAGE™ and other Allegion software or be integrated into popular physical access control and Proptech systems through Allegion's PACS Alliance program. This enables customers to choose what best fits their requirements now and in the future.

Standard features

- Next level design inside and out
- Credential support includes Schlage MIFARE®, Bluetooth® and NFC mobile¹
- Advanced encryption keeps data and communications safe
- Wireless configuration using connected smartphones or tablets
- No-Tour or offline system capacity
- Open architecture – interoperable and simple for software alliances to integrate
- Works seamlessly with other Schlage wireless locks, including Schlage Control®²
- Uniquely concealed key override standard on all locks

1. Use of mobile credential is dependent on availability of compatible mobile credential.
2. Check with your Proptech or PACS provider for specific support.

Mechanical specifications

Chassis	Exit trim, wide stile	Construction	All-metal chassis and escutcheon; exterior polycarbonate elements
Handing	On-site handing with included hex key	Cylinder and keys	Schlage Classic C keyway, Conventional 6-pin cylinder with two keys
Latch	Defined by exit device	Certifications	ANSI/BHMA A156.13-2020 Grade 1 ANSI/BHMA A156.25-2023 Locked outdoor type ANSI/BHMA A156.5-2020
Strike	Defined by exit device		
Strike width	Minimum 4-1/4" (108mm)		
Backset	Defined by exit device		
Door range	1-3/4" (44mm)		
Levers	Zinc		

Reader specifications

Credential technologies	Smart (13.56 MHz), Bluetooth Low Energy (LE) (2.4 GHz), and Near Field Communication (NFC)	Smart credential support	Secure application area: Schlage MIFARE Classic®, Schlage MIFARE® DESFire® EV1/EV2/EV3 CSN only: HID iCLASS®, HID iCLASS SE®, MIFARE Classic / DESFire
Read range	Smart: up to .5" Bluetooth® Low Energy: up to 15' NFC: mobile device dependent	Mobile credential support	Schlage Mobile Bluetooth Credential, Integrated PACS mobile credential with Bluetooth, Apple Wallet® NFC student ID and employee badge; Google Wallet™ NFC student ID and employee badge
Standards	ISO standard 15693 and ISO 14443		



XE360™ SERIES WIRELESS EXIT WIDE STILE LOCK

SELECT LOCK MODEL		
Description	Specify	Price (ea.)
Exit Trim with Wide Escutcheon	XE360-EW	\$1,379.00

SELECT EXIT ADAPTER		
Description	Specify	Price adjustment
Falcon 25 Rim	25R	No charge
Falcon 25 Surface Vertical Rod	25S	No charge
Von Duprin 98/99 or XP98/99 Rim	99R	No charge
Von Duprin 98/99 Surface Vertical Rod	99S	No charge
Von Duprin 22 Rim	22R	No charge
Von Duprin 22 Surface Vertical Rod	22S	No charge
Less Exit Adapter	LLL	-\$99.00

SELECT LOCK MODEL		
Description	Specify	Price adjustment
Offline – Toured and No-Tour compatible	OF	No charge

SELECT FUNCTION		
Description	Specify	Price adjustment
Indicator (LED indicator on interior assembly)	I	No charge
Button (Interior Push Button with LED indicator)	B	No charge

SELECT READER		
Description	Specify	Price adjustment
Smart / NFC Mobile (13.56 MHz) and Bluetooth® (2.4 GHz) Mobile Credential Support	SM	No charge

SELECT LEVER STYLE		
Description	Specify	Price adjustment
Broadway	BRW	No charge
Latitude	LAT	No charge
Neptune	NEP	No charge
Longitude Extended Length	LON-E	No charge

SELECT FINISH		
Description	Specify	Price adjustment
Satin Nickel	619	No charge
Matte Black	622	No charge
Satin Chrome	626	No charge



XE360™ SERIES WIRELESS EXIT WIDE STILE LOCK

SELECT KEY CYLINDER		
Description	Specify	Price adjustment
Schlage Conventional, 6-pin	P6	No charge

SELECT KEYWAY		
Description	Specify	Price adjustment
Schlage Classic Obverse	C	No charge

SELECT DOOR THICKNESS		
Description	Specify	Price adjustment
1-3/4" Thick door	134	No charge

SELECT DOOR POSITION SWITCH		
Description	Specify	Price adjustment
Less door position switch – Standard	LLL	No charge

SELECT SOLD SEPARATE		
Description	Specify	Price (ea.)
Mount, XE360 Series Exit Trim, for Falcon 25 rim (use Falcon 25 rim center case and center case cover kits to complete installation)	47709954	\$281.00
Condensation sealant kit (includes PCBA cover, backplate plugs, and gaskets for environmental robustness)	47870662	\$55.00
Door position switch	47467230	\$45.00
Exit device decorative plate kit (exterior: 13.87" x 3.75"; interior: 12.75" x 3.75")	47679797	\$49.50